


C-1000 SERIES NO-LEAD YARD HYDRANTS

SPECIFICATION:

- All-Weather Powder Coat Finish on head casting and lever provides resistance to corrosion, UV and abrasion.
- Heavy-duty, thick-walled head casting with bucket hook and removable 3/4" No-Lead Hose Thread Adapter
- Unique lever control to provide variable flow, rather than using a manual "lock", that could rust, to set the flow. Easy to grip, heavy duty handle.
- Stainless steel operating stem is polished, which will not cut the Teflon™ packing and packing nut, resulting in longest operating life.
- Pivot connector and nuts replaces set screws, that tend to be unreliable. This results in years of easy reliable adjustments.
- Draw Straps are made of high-strength 1040 hot-rolled steel that reduces wear and eliminates side pull on the operating rod, resulting in longer life.
- 1" galvanized standpipe where there are no exposed threads on the pipe where it meets the valve body. The threads are coated with bitumastic to prevent rusting underground and extending the life of the hydrant.
- Heavy-duty, thick-walled valve body, making it strong and resistant to breakage. Dual bypass design results in high flow rate. There is an 1/8" FPT tapped drain hole that allows the water in the standpipe to self-drain when hydrant is turned off, making the head and standpipe frost proof in even the coldest of weather.
- 3/8-16UNC galvanized operating rod
- Self-lubricating plunger prevents rubber from bonding to the valve body, with the longest operating life in a one-piece design.



Certified to NSF/ANSI/CAN 372




- Max Pressure: 100 PSI
- Max Temperature: 120°F

CERTIFICATION:

- NSF/ANSI/CAN 372 Certified
- ASTM A53 Sch 40 StandPipe

MATERIAL LIST	
Part Name	Material
Head	Cast Iron
Handle	Cast Iron
Lever Bolt & Nut	Zinc Plated Steel
Draw Straps	1040 Rolled Steel
Pivot Connector & Nuts	Zinc Plated Steel
Packing Nut	Brass
Valve Stem Packing	Teflon
O-Ring	Buna
Valve Body	No Lead Brass
Operating Stem	Stainless Steel
Rod Reducer	Brass
Operating Rod	Galvanized Steel
Stand Pipe	ASTM A53 Sch 40 Galvanized Steel
Plunger	Brass and Proprietary Rubber Blend

DIMENSIONS				
Part No.	Bury Depth	Overall Length	Width	Weight (lbs)
CNL7501	1'	44.5"	8.16"	11
CNL75015	1-1/2'	50.5"	8.16"	12
CNL7502	2'	56.5"	8.16"	13
CNL7503	3'	68.5"	8.16"	15
CNL7504	4'	80.5"	8.16"	17
CNL7505	5'	92.5"	8.16"	19
CNL7506	6'	104.5"	8.16"	21
CNL7507	7'	116.5"	8.16"	23
CNL7508	8'	128.5"	8.16"	25
CNL7510	10'	152.5"	8.16"	29



315 Flindt Dr. | Storm Lake, Iowa 50588 | (800) 831-6962

Learn More at merrillmfg.com

